


PRO SERIES

REPLACEMENT WINDOWS



100 SLIDING WINDOW



BUILT TO LAST. MADE TO IMPRESS.

You have a vision for how you want your replacement windows to look. Ply Gem Windows Pro Series can help you realize that vision. Every window is designed to fit your needs. You'll find the right sizes, the right designs and the right solutions to help make your window replacement project a success.



* This product can be configured to meet or exceed Federal Energy Tax Credit requirements.



100 SLIDING WINDOW



STANDARD FEATURES

- Single wall flush fin for specialty applications and enduring beauty
- Maintenance-free multi-chamber PVC construction with fusion welded corners for durability, weather-tight performance and beauty
- Specially designed rollers and improved pull rails allow easy, fingertip operation
- Secondary sash stop opens to a fixed point for ventilation
- Continuous weatherstripping and dual action sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient warm edge insulating glass for enhanced energy performance
- Operable sash lifts out for easy glass cleaning from inside
- Closed and locked sashes cannot be removed from exterior for added security
- 3 1/4" frame depth with heavy vinyl walls for strength and stability
- Equal sight lines for an unobstructed view of the beautiful outdoors



OPTIONS

GLASS OPTIONS:

HP glass, HP^{SC} glass, Warm Edge⁺, tints, obscure, tempered, laminated



GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat 5/8", sculptured 5/8" or 1" styles

HARDWARE OPTIONS:

Color-coordinated sash locks



FRAME OPTIONS:

Single wall flush fin, no fin, brick mould

COLOR OPTIONS:



THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Value	SHGC	VT
WITH WARM EDGE				
1 1/16" Clear	2.08	0.48	0.63	0.65
1 1/16" HP	3.33	0.30	0.29	0.55
1 1/16" HPP ^{SC}	3.33	0.29	0.22	0.43

All units tested in accordance with ASTM standards; rated in accordance with International Residential Code; and witnessed by an independent NAMI accredited lab. Performance values reflect the performance of units tested with the following configuration: 1 1/16" IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Most units rated DP30 standard.
2. Low-E with argon.
3. Optional Solar Cooling optimized Low-E with argon.
4. Optional Warm Edge+ spacer upgrade for enhanced performance.

